

BCC-MIL Classified SECURED COALITION COMMUNICATIONS

By BaseCampConnect



The BCC-MIL Classified is a portable secure communications system for Military & Coalition theatre operations.

The BCC-MIL Classified connects multi-technology networks and supports secure communication via SCIP and V.150.1. It has a standard 5 radio interoperability module. The module allows coalition encrypted-to-encrypted communications without sharing encryption keys.

Preset network connections and automatic failover. No computer or training needed to operate. Low wattage operation on 110V.

The BCC-MIL is fitted in a rugged hard case equipped with shock-mounts. All accessories are contained in a portable carrying case. This communications go-kit is perfect for military exercises and coalition operations.

Key features:

- DISA Certified Local Session Controller
- JTIC Certified
- Satellite ready
- Integrated network switch with 24 PoE LAN ports
- Encrypted-to-encrypted radio interoperability
- Extreme Conferencing, MLPP
- AS-SIP, SCIP, V.150.1, and TLS/SRTP
- Equipped with REDCOM SLICE® 2100
- Resilient to hard shutdowns
- Voice, video and chat
- Bridges cellular PTT to radio interface

PRINTED IN CANADA

WWW.BASECAMPCONNECT.COM

BCC-MIL CLASSIFIED SPECIFICATIONS

RADIO GATEWAY

Radio Interface: 5 Ports / Handset / Speaker Port / 2 Talk Groups

Radio Interface Cables: 5 Cables included

Compatibility: All frequency, encrypted and clear

DATA

LTE Broadband Router Dual SIM / DUAL modem

Number of Simultaneous Users: 128

7-to-1 DATA Antenna (4x LTE / 2x WiFi / GPS): Optional

Ethernet WAN: 2 (Satellite-ISP)

Switch: 24 ports PoE (VLAN) manageable

WiFi: 2.4 and 5ghz

SYSTEM CAPABILITIES

SIP Trunks: Up to bandwidth

Analog Extensions: Up to 48 analog line circuits

Digital Extensions (ISDN): Up to 4

SIP Extensions: Up to 2000 registered SIP subscribers per unit

T1/E1: Up to 8

UPS: Up to 15 minutes

Advanced Secure Gateway

Networks: DSN (ANSI 619a), PSTN, ISDN, SS7, R2, E1, E1 Priority

Wireless: Federal& Civil Radios, GSM

Secure Interoperability: SWT, SCIP, Iridium Type I, GSM Type I, STE, NBS, LTU-TED, Secure Tactical Radios

TRI-TAC Networks: Secure Dial, Secure Access, KY-68 2nd Dial, Red T1

MECHANICAL & ENVIRONMENT

Carrying Case: Rugged Military Grade Rackmount

Dimensions: 38.5" X 24.6" X 14.9" / 97.8cm X 62.5cm X 37.8cm

Weight: 110 lbs. / 50 kg

Operating Temperature: -10 to +50°C, 5-95% humidity

Storage temperature: -30 to +70°C, 0-90% humidity

Power Requirements: 110VAC (240VAC available)

2-year warranty

© 2019 Telflex Technologie inc. BCCMILC-07-29-2019



sales@basecampconnect.com

1.855.900.3539

WWW.BASECAMPCONNECT.COM